

Model	3500SLX	6000ELX
Lifting capacity	3,500 lbs / 1,588 kg	6,000 lbs / 2,722 kg
<b>A</b> Lowered height (frame only)	3" / 76 mm	3.5" / 89 mm
<b>B</b> Height, frame only *	16" / 404 mm	20.75" / 527 mm
<b>C</b> Height, small blocks	17" / 431 mm	21" / 533 mm
<b>D</b> Height, tall blocks	18" / 457 mm	21.75" / 552 mm
<b>E</b> Height, stacked blocks	21" / 533 mm	24.5" / 622 mm
<b>F</b> Frame width	10.5" / 267 mm	12.5" / 318 mm
<b>G</b> Max lifting point spread	50.5" / 1,283 mm	76" / 1,930 mm
<b>H</b> Min lifting point spread	27" / 686 mm	53" / 1,346 mm
<b>I</b> Frame length	62.5" / 1,588 mm	86.75" / 2,203 mm
Individual frame weight	60 lbs / 27 kg	112 lbs / 51 kg
Power unit weight (no fluid)	50 lbs / 23 kg	50 lbs / 23 kg
Power Unit PRV setting	2,400 psi	2,400 psi
Maximum Operating Pressure	2,100 psi	2,100 psi
Sound (when raising/lowering)	<70 dBA	<70 dBA
Maximum allowed wind speed	<60 mph / <96.5 kph	<60 mph / <96.5 kph

netto

**brutto**

1.395,00

**1.660,05**

1.950,00

**2.320,50**

**QUICKJACK Europa**

**Deutschlandbüro + Renndienst**



Michael H. Scheithauer

Handel u. Promotion von Accessoires für Automobilebhaber @ TACHETTO  
Postadresse: Matthias-Gesner-Straße 63 • 91154 Roth

Email: [hallo@der-schnelle-auto-heber.de](mailto:hallo@der-schnelle-auto-heber.de)

Tel: 0 91 71 / 89 55 60 4

Mobil: 0 155 / 66 79 12 13

**#quickjackMIKE**

<b>Model</b>	<b>5000TL</b>	<b>7000TL</b>	<b>5000TLX</b>	<b>7000TLX</b>
Lifting capacity	5,000 lbs / 2,268 kg	7,000 lbs / 3,175	5,000 lbs / 2,268 kg	7,000 lbs / 3,175 kg
<b>A</b> Lowered height (frame only)	3" / 76 mm	3.5" / 89 mm	3" / 76 mm	3.5" / 89 mm
<b>B</b> Height, frame only *	20.25" / 512 mm	20.75" / 527 mm	20.25" / 512 mm	20.75" / 527 mm
<b>C</b> Height, small blocks	20.5" / 520 mm	21" / 533 mm	20.5" / 520 mm	21" / 533 mm
<b>D</b> Height, tall blocks	21.5" / 546 mm	21.75" / 552 mm	21.5" / 546 mm	21.75" / 552 mm
<b>E</b> Height, stacked blocks	24" / 610 mm	24.5" / 622 mm	24" / 610 mm	24.5" / 622 mm
<b>F</b> Frame width	11" / 279 mm	12.5" / 318 mm	11" / 279 mm	12.5" / 318 mm
<b>G</b> Max lifting point spread	60" / 1,524 mm	60" / 1,524 mm	66" / 1,676 mm	66" / 1,676 mm
<b>H</b> Min lifting point spread	37" / 940 mm	37" / 940 mm	43" / 1,092 mm	43" / 1,092 mm
<b>I</b> Frame length	70" / 1,778 mm	70.75" / 1,797mm	76" / 1,930 mm	76" / 1,930 mm
Individual frame weight	78 lbs / 35 kg	98 lbs / 45 kg	81.5 lbs / 37 kg	103 lbs / 47 kg
Power unit weight (no fluid)	50 lbs / 23 kg	50 lbs / 23 kg	50 lbs / 23 kg	50 lbs / 23 kg
Power Unit PRV setting	2,400 psi	2,400 psi	2,400 psi	2,400 psi
Maximum Operating Pressure	2,100 psi	2,100 psi	2,100 psi	2,100 psi
Sound (when raising/lowering)	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Maximum allowed wind speed	<60 mph / <96.5 kph	<60 mph / <96.5 kph	<60 mph / <96.5 kph	<60 mph / <96.5 kph

netto

1.625,00

1.725,00

1.675,00

1.775,00

**brutto**

**1.933,75**

**2.052,75**

**1.993,25**

**2.112,25**